

MINI SCORPIO 23

CRANES

WHITES SPECIALTY EQUIPMENT

The Mini Scorpio 23 crane has a number of features that puts it in a league of its own. The Mini Scoprio 23 crane has an automatic arc compensator in both horizontal and vertical axis, programmable limits on the telescopic movement, repeatable

arm articulation, adjustable dampening, motorized weight tray and a variety of positional data for the operator or VFX team to name a few. Besides the electronic advantages of the Mini Scorpio 23 crane, it features the longest articulating arm that can be wheeled through a typical 34"x7' door and is adjustable to fit standard; 62cm, 88cm, and 1m track. WFW has a wide range of stabilized and standard two and three axis remote heads, ideal for use with the Mini Scorpio 23 crane.



Mini Scorpio 23 Quick Specs

Max. lens height (underslung)	21'	6.7m
Max. lens height (overslung)	26'2"	8.0m
Max. reach from fulcrum	23'	<i>7</i> .1 m
Min. reach from fulcrum	5'	1.5m
Max. overall length	29'	8.9m
Min. overall length	10'10"	3.3m
Min. height at fulcrum	6'5"	1.97m
Fulcrum travel	12"	0.3m
Length of base (smallest to 1m track)	5'6"-6'2"	1. <i>7</i> -1.9m
Width of base (smallest to 1m track)	2'11"-5'6"	1.0-1.7m
Weight (unladen)	1100lbs	335kg

Partners in Production®

VANCOUVER CALGARY REGINA WINNIPEG TORONTO HALIFAX